

# Contents

<b>1</b>	<b>Introduction and Overview</b>	<b>1 - 1</b>
1.1	Context of the Present Study	1 - 1
1.2	Expected Performance and Parameters	1 - 2
1.2.1	Components	1 - 3
1.2.2	Performance	1 - 8
1.2.3	Conclusions	1 - 10
1.3	Physics Motivation	1 - 10
1.3.1	Evidence for Neutrino Oscillations	1 - 10
1.3.2	Neutrino Oscillation Formalism	1 - 11
1.3.3	Types of Neutrino Masses, Seesaw Mechanism	1 - 14
1.3.4	Tests for Neutrino Masses in Decays	1 - 19
1.3.5	Models for Neutrino Masses and Mixing	1 - 19
1.3.6	Lepton Mixing	1 - 20
1.3.7	Relevant Near- and Mid-Term Experiments	1 - 22
1.3.8	Oscillation Experiments at a Neutrino Factory	1 - 23
1.3.9	Matter Effects	1 - 25
1.4	CP Violation	1 - 26
1.4.1	Detector Considerations	1 - 27
1.4.2	Experiments with a High-Intensity Conventional Neutrino Beam	1 - 27
1.4.3	Uses of Intense Low-Energy Muon Beams	1 - 28
1.4.4	Conclusions	1 - 29
<b>2</b>	<b>Proton Driver</b>	<b>2 - 1</b>
2.1	The AGS as a Proton Driver	2 - 1
2.2	Superconducting Linac (SCL)	2 - 7
2.3	AGS Main Power Supply Upgrade	2 - 9
2.3.1	Present Mode of Operation	2 - 9

2.3.2	Neutrino Factory Mode of Operation . . . . .	2 - 10
2.4	AGS rf System Upgrade . . . . .	2 - 11
2.5	Conclusions . . . . .	2 - 14
<b>3</b>	<b>Target System and Support Facility</b>	<b>3 - 1</b>
3.1	Introduction . . . . .	3 - 1
3.1.1	Overview . . . . .	3 - 1
3.1.2	Target System Layout . . . . .	3 - 3
3.1.3	Capture and Matching Solenoids . . . . .	3 - 5
3.1.4	Magnetic Disruption of the Mercury Jet . . . . .	3 - 6
3.1.5	Mercury Containment . . . . .	3 - 8
3.1.6	Target System Support Facility . . . . .	3 - 8
3.2	Calculations of Pion Yield and Radiation Dose Using MARS . . . . .	3 - 9
3.2.1	Captured Pion/Muon Beam <i>vs.</i> Target and Beam Parameters . . . . .	3 - 10
3.2.2	Particle Fluxes, Power Density and Radiation Dose . . . . .	3 - 12
3.3	Calculations of Energy Deposition and Activation Using MCNPX . . . . .	3 - 13
3.3.1	Energy Deposition . . . . .	3 - 16
3.3.2	Activation Analysis . . . . .	3 - 17
3.3.3	Radial Leakage of Radiation from the Target Module . . . . .	3 - 23
3.4	Pion Capture Magnet . . . . .	3 - 24
3.4.1	Hollow-Conductor Resistive Coils . . . . .	3 - 28
3.4.2	Superconducting Coils . . . . .	3 - 34
3.4.3	Magnetic Forces . . . . .	3 - 37
3.4.4	Field Quality . . . . .	3 - 38
3.5	Beam Windows . . . . .	3 - 38
3.5.1	Upstream Proton Beam Window . . . . .	3 - 38
3.5.2	Downstream Beam Window . . . . .	3 - 42
3.6	Mercury Deflectors . . . . .	3 - 43
3.6.1	Mercury Jet Nozzle . . . . .	3 - 43
3.6.2	Entrance Baffles to the Mercury Pool . . . . .	3 - 44
3.7	Mercury Flow Loop . . . . .	3 - 44
3.7.1	Process Flow Loop and Absorber . . . . .	3 - 46
3.7.2	Target System Maintenance . . . . .	3 - 47
3.8	Target Support Facility . . . . .	3 - 49
3.8.1	Solenoid Magnets . . . . .	3 - 52
3.8.2	Assembly and Installation . . . . .	3 - 54
3.8.3	High-Field Region . . . . .	3 - 54
3.8.4	Coil-to-Coil Forces, Method of Support and of Assembly . . . . .	3 - 56

3.8.5	Decay Channel Coils . . . . .	3 - 57
3.8.6	Coil Replacement and Remote Handling . . . . .	3 - 58
3.8.7	Facility Shielding . . . . .	3 - 59
3.8.8	Maintenance Operations . . . . .	3 - 60
3.9	Target System Summary . . . . .	3 - 60
<b>4</b>	<b>Decay and Phase Rotation Channel</b>	<b>4 - 1</b>
4.1	Concept . . . . .	4 - 1
4.2	Drift Sections . . . . .	4 - 2
4.3	Induction Linacs . . . . .	4 - 6
4.4	The Solenoids . . . . .	4 - 6
4.5	Minicooling Absorbers . . . . .	4 - 8
4.5.1	Handling the Average Heat Load . . . . .	4 - 8
4.5.2	Handling the Peak Power Density . . . . .	4 - 10
4.5.3	Window Design . . . . .	4 - 10
4.6	Summary . . . . .	4 - 12
<b>5</b>	<b>Buncher and Ionization Cooling</b>	<b>5 - 1</b>
5.1	Matching from Induction Linac to Buncher . . . . .	5 - 1
5.1.1	The Transverse Matching Section . . . . .	5 - 2
5.2	Buncher Section . . . . .	5 - 4
5.2.1	Longitudinal-Transverse Correlation . . . . .	5 - 7
5.3	Ionization Cooling Channel . . . . .	5 - 7
5.3.1	Principle of Ionization Cooling . . . . .	5 - 7
5.3.2	Concept of the Tapered SFOFO Cooling Channel . . . . .	5 - 10
5.3.3	Description of the SFOFO Cooling Channel . . . . .	5 - 15
5.3.4	Performance . . . . .	5 - 22
5.3.5	Tolerances & Systematics . . . . .	5 - 27
5.3.6	Liquid Hydrogen Absorbers . . . . .	5 - 33
5.3.7	Diagnostics and Instrumentation Issues in the Cooling Channel . . . . .	5 - 36
5.3.8	Engineering Considerations . . . . .	5 - 44
5.4	Conclusion: Performance of the Entire Front End . . . . .	5 - 48
5.5	Matching Cooling to Acceleration . . . . .	5 - 51
5.5.1	Method . . . . .	5 - 51
5.5.2	RF Cavities . . . . .	5 - 51
5.5.3	Superconducting Coils . . . . .	5 - 51
5.5.4	ICOOL Simulation . . . . .	5 - 53

<b>6</b>	<b>Acceleration: Recirculating Linear Accelerator</b>	<b>6 - 1</b>
6.1	Linear Accelerator . . . . .	6 - 4
6.1.1	Matching . . . . .	6 - 4
6.1.2	Linac General Parameters and Lattice Period Layout . . . . .	6 - 4
6.1.3	Longitudinal Beam Dynamics . . . . .	6 - 10
6.1.4	Transverse Beam Dynamics and Tracking . . . . .	6 - 12
6.1.5	Injection Chicane . . . . .	6 - 15
6.1.6	Solenoid Magnets . . . . .	6 - 18
6.2	Recirculating Linac (RLA) . . . . .	6 - 19
6.2.1	Arc Optics, Spreaders, and Recombiners: Design Choices . . . . .	6 - 19
6.2.2	Longitudinal Dynamics in Recirculating Linac . . . . .	6 - 20
6.2.3	General Parameters and Period Layout of RLA Linac . . . . .	6 - 22
6.2.4	Beam Dynamics in the RLA Linacs . . . . .	6 - 27
6.2.5	Odd Arcs: Proof-of-principle Lattice Design . . . . .	6 - 29
<b>7</b>	<b>Muon Storage Ring</b>	<b>7 - 1</b>
7.1	Overall Design Motivation . . . . .	7 - 1
7.1.1	Design Choices for Optimizing Arcs . . . . .	7 - 3
7.1.2	Choice of Straight Length . . . . .	7 - 4
7.1.3	Lattice Parameters . . . . .	7 - 5
7.2	The Lattice . . . . .	7 - 6
7.2.1	Effect of Magnet Choice on Lattice Design . . . . .	7 - 6
7.2.2	Lattice Design . . . . .	7 - 8
7.2.3	Chromatic Correction Sextupoles . . . . .	7 - 10
7.2.4	Coil End Effects . . . . .	7 - 11
7.2.5	Correction and Tuning . . . . .	7 - 13
7.2.6	Tracking . . . . .	7 - 13
7.3	Magnets . . . . .	7 - 19
7.3.1	Magnetic Design . . . . .	7 - 23
7.4	Beam Flux to Detector . . . . .	7 - 24
7.5	Instrumentation . . . . .	7 - 27
<b>8</b>	<b>High-Power RF systems: 201.25 and 402.5 MHz</b>	<b>8 - 1</b>
8.1	Introduction to rf Systems . . . . .	8 - 1
8.2	NCRF Specifications for Buncher and Cooling . . . . .	8 - 2
8.3	RF Station Description . . . . .	8 - 2
8.3.1	Power Source and Equipment . . . . .	8 - 4
8.3.2	Station Controls and Low-Level rf . . . . .	8 - 8

8.3.3	High-Voltage Modulator and Power Supply . . . . .	8 - 8
8.3.4	NCRF AC Electrical Power and Water System . . . . .	8 - 10
8.4	Specification of NCRF Cavities for Cooling . . . . .	8 - 11
8.4.1	201.25 MHz Closed-Cell Description . . . . .	8 - 11
8.4.2	Foil Requirements . . . . .	8 - 13
8.4.3	2.75 m Lattice Implementation (Lattice 1) . . . . .	8 - 21
8.4.4	1.65 m Lattice Implementation (Lattice 2) . . . . .	8 - 21
8.4.5	402.5 MHz Buncher Cavity . . . . .	8 - 23
8.4.6	Tuning Requirements . . . . .	8 - 24
8.4.7	Vacuum Requirements . . . . .	8 - 25
8.5	SCRF Cavities for Acceleration . . . . .	8 - 25
8.5.1	SCRF Structures at 201.25 MHz . . . . .	8 - 29
8.5.2	Input Power Coupler . . . . .	8 - 30
8.5.3	Higher-Order Mode (HOM) Couplers . . . . .	8 - 33
8.5.4	Tuner . . . . .	8 - 34
8.5.5	Cryogenics for SCRF . . . . .	8 - 36
8.5.6	Power Source for SCRF . . . . .	8 - 38
8.6	Conclusions . . . . .	8 - 40
<b>9</b>	<b>Induction Linac</b> . . . . .	<b>9 - 1</b>
9.1	Induction Accelerators for the Phase Rotator System . . . . .	9 - 1
9.1.1	Accelerator Waveforms . . . . .	9 - 2
9.1.2	Magnetic Material . . . . .	9 - 3
9.1.3	Induction Linac 1 Cell . . . . .	9 - 5
9.1.4	Induction Linac 2 Cell . . . . .	9 - 8
9.1.5	Induction Linac 3 Cell . . . . .	9 - 12
9.1.6	Pulsing System . . . . .	9 - 13
9.1.7	Mechanical Systems . . . . .	9 - 19
<b>10</b>	<b>Superconducting Solenoid Magnets</b> . . . . .	<b>10 - 1</b>
10.1	Introduction . . . . .	10 - 1
10.2	Decay and Phase Rotation Channel Solenoids . . . . .	10 - 1
10.2.1	Stray Fields . . . . .	10 - 10
10.3	Buncher and Cooling Channel Solenoids . . . . .	10 - 11
10.3.1	Solenoid Layout and Parameters . . . . .	10 - 11
10.3.2	Forces . . . . .	10 - 13
10.3.3	Conductor . . . . .	10 - 16
10.3.4	Refrigeration . . . . .	10 - 17

10.3.5	Quench Protection . . . . .	10 - 20
10.3.6	Alignment . . . . .	10 - 20
10.3.7	Magnetic Field Outside the Solenoids . . . . .	10 - 21
10.4	Linear Accelerator Solenoids . . . . .	10 - 21
<b>11</b>	<b>Cryogenic Systems</b>	<b>11 - 1</b>
11.1	Introduction . . . . .	11 - 1
11.2	Cooled Components . . . . .	11 - 1
11.3	Component Loads . . . . .	11 - 5
11.4	Refrigeration Selection . . . . .	11 - 6
11.5	Capital Cost, Installation, and Operation . . . . .	11 - 8
11.5.1	Capital Cost . . . . .	11 - 8
11.6	Operational Issues . . . . .	11 - 9
11.6.1	Power, Operations Labor, Maintenance . . . . .	11 - 9
11.6.2	Cryogenic Safety . . . . .	11 - 10
<b>12</b>	<b>Conventional Facilities</b>	<b>12 - 1</b>
12.1	Introduction . . . . .	12 - 1
12.2	Structures . . . . .	12 - 1
12.2.1	Transport Tunnel and Egress Spurs . . . . .	12 - 1
12.2.2	Support Buildings . . . . .	12 - 2
12.3	Soils, Earthwork, and Shielding . . . . .	12 - 2
12.4	Conventional Power . . . . .	12 - 3
12.5	Cooling Water . . . . .	12 - 3
12.6	Site Improvements . . . . .	12 - 3
<b>13</b>	<b>Environment, Safety and Health Considerations</b>	<b>13 - 1</b>
13.1	Introduction . . . . .	13 - 1
13.2	Procedural/Regulatory Matters . . . . .	13 - 1
13.2.1	Environmental Protection . . . . .	13 - 2
13.2.2	Environment Regulatory Compliance . . . . .	13 - 2
13.3	Occupational Safety During Construction of the Facility . . . . .	13 - 3
13.4	Environmental Protection During the Construction of the Facility . . . . .	13 - 3
13.4.1	Ordinary Operational Occupational Safety Hazards . . . . .	13 - 4
13.5	Novel Occupational Safety Hazards . . . . .	13 - 4
13.5.1	Use of Nonflammable Cryogenes . . . . .	13 - 4
13.5.2	Use of Flammable Cryogenes . . . . .	13 - 4
13.5.3	Muon Storage Ring Life Safety (Egress) Considerations . . . . .	13 - 5

13.5.4 Muon Storage Ring Slope Hazards . . . . .	13 - 5
13.6 Prompt and Residual Radiation Safety . . . . .	13 - 6
13.6.1 Proton Driver . . . . .	13 - 6
13.6.2 Cooling Stages and Muon Acceleration Stages . . . . .	13 - 10
13.6.3 Muon Storage Ring . . . . .	13 - 10
13.7 Non-Radiological Environmental Protection Issues . . . . .	13 - 13
13.7.1 Proton Driver, Target Station, Cooling and Acceleration . . . . .	13 - 13
13.7.2 Muon Storage Ring . . . . .	13 - 13
13.8 Summary . . . . .	13 - 13
<b>14 R&amp;D Plans</b>	<b>14 - 1</b>
14.1 Introduction . . . . .	14 - 1
14.2 Proton Driver . . . . .	14 - 2
14.3 Target System . . . . .	14 - 2
14.4 Phase Rotation and Capture . . . . .	14 - 4
14.5 Buncher and Cooling . . . . .	14 - 6
14.6 Acceleration System . . . . .	14 - 11
14.7 Storage Ring . . . . .	14 - 19
<b>15 Detectors</b>	<b>15 - 1</b>
15.1 Introduction . . . . .	15 - 1
15.2 Beam Parameters . . . . .	15 - 2
15.3 Physics Signals . . . . .	15 - 2
15.4 Long Baseline Oscillation Experiment . . . . .	15 - 3
15.5 Detector Options . . . . .	15 - 9
15.6 WIPP Site . . . . .	15 - 11
15.7 The Near Detector . . . . .	15 - 13
15.8 Summary . . . . .	15 - 15
<b>A Cost Estimates</b>	<b>A - 1</b>
A.1 Methodology and Facility Costs . . . . .	A - 1
A.2 Cost Reduction Options . . . . .	A - 5
A.2.1 Introduction . . . . .	A - 5
A.2.2 Capture Solenoid . . . . .	A - 6
A.2.3 Bitter Magnet . . . . .	A - 7
A.2.4 Phase Rotation . . . . .	A - 10
A.2.5 Cooling . . . . .	A - 13
A.2.6 Summary . . . . .	A - 15

<b>B</b>	<b>Options</b>	<b>B - 1</b>
B.1	Proton Driver	B - 1
B.1.1	Increasing Power to 2 or 4 MW	B - 1
B.1.2	Proton Bunch Length and a Buncher Ring	B - 4
B.2	Target	B - 5
B.2.1	Rotating Inconel Band Option	B - 5
B.2.2	Carbon	B - 11
B.2.3	Granular	B - 12
B.3	Phase Rotation	B - 12
B.3.1	Correlation Matching	B - 12
B.3.2	Polarization	B - 13
B.3.3	Bunched Beam Phase Rotation	B - 13
B.4	Cooling	B - 14
B.4.1	Limited-Flip Cooling Channels	B - 14
B.4.2	The Double-Flip Cooling Channel	B - 15
B.4.3	Emittance Exchange	B - 39
B.4.4	NCRF: Grid of Tubes Alternative to Foil Windows.	B - 40
B.5	Acceleration	B - 40
B.5.1	Accelerator Acceptance.	B - 40
B.5.2	Dogbone Configuration	B - 41
B.6	Detector	B - 42
B.6.1	Introduction	B - 42
B.6.2	Site	B - 44
B.6.3	Detector	B - 44